

# Cable Screw Glands acc. to DIN 46320, PG 36

Kabelverschraubung IP54 DIN 46320

**Product number** 50107

**Weight** 0.586kg



Illustrations are for reference only.  
Technical specifications may vary and  
are subject to change without notice.

## Product description

- DIN 46320 for normal applications with soft rubber gasket
- due to the risk of formation of strain fissures the lateral stress on the gland and higher turning moment are to be avoided
- material: impactresistant Polystyrol
- colour: grey RAL 7035
- protection spec.: installation with connection thread gasket IP 66
- temperature resistance: -25 °C up to max. +60 °C

## Product properties

<b>GL</b>	13 mm
<b>Thread type</b>	PG
<b>DIN</b>	DIN 46320
<b>Protection spec.</b>	IP 54
<b>Colour</b>	grade (RAL 7035)
<b>Temperature resistant</b>	-20 °C - 60 °C
<b>min. - max. cable diameter</b>	25 - 32 mm
<b>Type of packaging</b>	10
<b>Version</b>	Impact resistant
<b>Nominal size</b>	PG 36
<b>Thread (AG)</b>	PG 36
<b>Key size</b>	50 / 53 mm
<b>Material</b>	Polystyrene
<b>H</b>	39 mm

More images

