

# HIL-SHRINK® XTF spool 2:1 Heat Shrinkable Tubing 9,5/4,8 clear

Spule

**Product number** 32267

**Weight** 1.389kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

## Product description

Zero halogen general purpose heat shrinkable tubing for insulation and protection. Self-extinguishing. Approval to standard UL 224 (except clear tubings)

- shrink ratio: 2:1
- permanent operating temperature: -55 °C up to +125 °C
- material: polyolefin
- shrink temperature: +125 °C
- UL
- zero halogen

## Product properties

|                                         |                                   |
|-----------------------------------------|-----------------------------------|
| <b>max after shrink operation Ø d</b>   | 4,8 mm                            |
| <b>min. at delivery Ø D</b>             | 3/8 Zoll                          |
| <b>Type of packaging</b>                | 75                                |
| <b>Huges after shrink op. s</b>         | 0,56 mm                           |
| <b>Shrinking temperature</b>            | 125 °C                            |
| <b>Shrink ratio</b>                     | 2:1                               |
| <b>Material</b>                         | Polyolefin                        |
| <b>Continuous operating temperature</b> | -55 °C – 125 °C                   |
| <b>Flexibility</b>                      | thin-walled                       |
| <b>Colour</b>                           | transparent                       |
| <b>material properties</b>              | self-extinguishing , halogen-free |
| <b>min. at delivery Ø D</b>             | 9,5 mm                            |
| <b>Version</b>                          | Coil                              |

## More images

