

# HIL-BOX® enclosure system including stepped entry seals, nylon-hinged screws, 300 x 220 x 120 mm

Stufennippel

**Product number** 55420

**Weight** 1.157kg



Illustrations are for reference only.  
Technical specifications may vary and are subject to change without notice.

## Product description

Shock resistant enclosure including universal entry seals in soft material with different diameters. Cover fixed with nylon screws. The unscrewing of the nylon screws allows to open the lid in 2 directions depending of the used screws. The screws are used as hinge and allows fast opening of the enclosure.

- Protection spec.: IP 55 acc. DIN EN 60529
- Material: base and lid ABS (UV resistant), entry seals PVC, screws PA
- Installation temp.: -15 °C up to +60 °C DIN EN 60670
- Temperature resistance: max. 70 °C acc. DIN EN 60695-10-2
- Flame protection: 650 °C acc. DIN EN 60695-2-11

### Further information:

- Screws included

## Product properties

<b>G</b>	80 mm
<b>C</b>	120 mm
<b>Type of packaging</b>	1
<b>D</b>	50 mm
<b>Diameter nipples</b>	14 - 32 mm
<b>DIN</b>	DIN EN 60529
<b>b</b>	220 mm
<b>Nipples</b>	12
<b>A</b>	300 mm
<b>Protection spec.</b>	IP 55

## More images

