

EMC Cable Screw Gland, UNI HF Dicht, PG 16 EMC, 6,5 - 9,5 cable

EMV-Kabelverschraubung UNI HF Dicht

Product number 52070

Weight 2.359kg



Illustrations are for reference only.
Technical specifications may vary and
are subject to change without notice.

Product description

The functional effect of the gland is only achieved by a low-ohm transition resistance between the cable and line leads and the wall of the electrical unit, i. e. clean the contact surfaces or even better provide, permanent bonding from inside by fitting lock nuts with equipotential bonding.

- with sealing out of TPE
- material: brass, nickel-plated
- protection spec.: IP 68 up to 10 bar
- temperature resistance: -20 °C up to +105 °C

Further information:

- **Index A:** stripped cable sheath
- **Index B:** continuous cable sheath

Product properties

min. - max. cable diameter	9,5 - 6,5 mm
H	21 mm
Thread type	PG
Protection spec.	IP 68
Sealing insert material	TPE
Version	with iris feather
Type of packaging	50
Cable sheath	abgesetzt
Thread (AG)	PG 16
GL	6,5 mm
Screen diameter max.-min.	8 - 3,5 mm
Temperature resistant	-20 °C - 105 °C
Material	Nickel-plated brass

More images

