

HIL-SHRINK® 3:1 CCB Heat Shrinkable Tubing Adhesive lined heat shrinkable cable breakouts. Flame retardant 100,0/47 black

CCB 3:1 dickwandig, schwer entflammbar, Abzweigmuffen

Product number 34670

Weight 1.402kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

Product description

Adhesive lined heatshrinkable cable breakouts

- permanent operating temperature: -30 °C up to +70 °C
- material: polyolefin cross-linked
- shrink temperature: +120 °C

Further Information:

- flame retardant

Product properties

| | |
|---|-----------------------------------|
| Delivery condition L | 173 mm |
| min. at delivery Ø D1 | 95 mm |
| Shrinking temperature | 120 °C |
| Shrink ratio | 3:1 |
| max after shrink operation Ø D2 | 14 mm |
| Colour | black |
| Number of Piggyback Adapters | 4 |
| Material | Polyolefin radiation cross-linked |
| min. at delivery Ø D2 | 35 mm |
| material properties | stiff , flame retardant |
| after shrinking L | 222 mm |
| Type of packaging | 10 |
| max after shrink operation Ø D1 | 36 mm |
| Continuous operating temperature | -30 °C – 70 °C |
| Flexibility | thick-walled |

More images

