

# Spacing insulator type CPE, M10, red, 100 mm

TYP CPE

**Product number** 90149

**Weight** 2.808kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

## Product description

- made of polyglass-polyester material
- reinforced fibre glass
- self extinguishing
- operating temperature: -40 °C to +130 °C
- fire resistance: UL94-V0
- threaded bolt: galvanised steel
- UM = max. operating voltage

## Product properties

|  |  |
|--|--|
| <b>U<sub>M</sub></b>                   | 8000 V   |
| <b>Diameter</b>                        | 60 mm  |
| <b>max. bending force</b>              | 15 kN  |
| <b>Threaded bolt material</b>          | Galvanized steel                                 |
| <b>Colour</b>                          | red  |
| <b>max. pulling force</b>              | 35 kN  |
| <b>Insulation material properties</b>  | self-extinguishing , Reinforced with glass fiber |
| <b>max. pressure-carrying capacity</b> | 150 kN   |
| <b>max. indicate torque</b>            | 24 - 55 Nm                                       |
| <b>Insulation material</b>             | Polyglass-polyester compound                     |
| <b>Flame retardancy</b>                | UL 94 V-0  |
| <b>Temperature resistant</b>           | -40 °C – 130 °C                                  |
| <b>H</b>                               | 100 mm   |
| <b>SW</b>                              | 60 mm  |
| <b>Discharge voltage</b>               | 50 kV  |
| <b>Type of packaging</b>               | 5  |
| <b>A</b>                               | 19 mm  |
| <b>Thread (M)</b>                      | M10  |
| <b>Typ</b>                             | CPE 100  |
| <b>Creep strength</b>                  | 35 kV  |

## More images

