

# HP VENT-LINE cable glands, brass nickel-plated, M 25 x 1,5 MS

Ventline Kabelverschraubung Messing

**Product number** 57001

**Weight** 0.081kg



Illustrations are for reference only.  
Technical specifications may vary and  
are subject to change without notice.

## Product description

- material: cable gland: brass nickel-plated, stainless steel, polyamide
- seal: EPDM
- membrane: ePTFE
- protection class: IP 68 to 0,6 bar (to EN 60 529)
- temperature range: -40 °C up to 100 °C, temporarily up to approx. +120 °C

## Product properties

<b>I</b>	7 mm
<b>Protection spec.</b>	IP 68
<b>Type of packaging</b>	1
<b>Temperature resistant</b>	-40 °C - 100 °C
<b>min. - max. cable diameter</b>	9 - 17 mm
<b>Thread type</b>	metric
<b>TL</b>	43 - 52 mm
<b>Thread (AG)</b>	M 25 x 1,5
<b>SW</b>	29 mm
<b>E1</b>	32 mm
<b>Material</b>	Nickel-plated brass

More images



luftdichtes Gehäuse gegenüber dem Verschluss

Innendruck p (bar)	M20 (l/min.)	M25 (l/min.)	M32 (l/min.)
0,07	0,13	0,16	0,19
0,10	0,15	0,20	0,25
0,20	0,26	0,37	0,46
0,30	0,36	0,54	0,67
0,40	0,47	0,71	0,89
0,50	0,57	0,88	1,11
0,60	0,68	1,05	1,33
0,70	0,79	1,22	1,59
0,80	0,89	1,42	1,82
0,90	1,01	1,60	2,05
1,00	1,12	1,79	2,22

