

# HIL-QUICK® Ring Terminal, insulated, Polycarbonate, A 4 - 6,0, 1000 pcs. | 1000

\$\$\$Marke\$\$\$ Quetschkabelschuh Ringform, \$\$Isolierstoff\$\$,  
\$\$Nennquerschnitt\_qmm\$\$, \$\$Verpackungsart\_Stk\$\$\$

**Product number** 10020 HQ

**Weight** 1.544kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

## Product description

- acc. to DIN 46237
- with flared insulation
- suitable for harmonized wires
- insulation: polycarbonate
- temperature range: -10 °C up to +105 °C
- zero halogen
- UL approved

## Product properties

<b>d4</b>	6,5 mm
<b>Brand</b>	Hil-Quick®
<b>d2</b>	4,3 mm
<b>DIN</b>	DIN 46237
<b>Nominal cross section</b>	> 2,5 - 6 mm <sup>2</sup>
<b>Material thickness</b>	1 mm
<b>UL-Approval</b>	Yes
<b>Colour</b>	yellow
<b>Temperature resistant</b>	-10 °C – 105 °C
<b>Type of packaging</b>	1000
<b>a1</b>	6 mm
<b>Insulation material</b>	Polycarbonate
<b>Nominal size</b>	A - 4 - 6,0 DIN
<b>l</b>	22,15 mm
<b>a2</b>	14,15 mm
<b>Version</b>	soldered
<b>d3</b>	8 mm
<b>Insulation material properties</b>	halogen-free

## More images

