

# Spacing insulator type DP/P, M6, red, 35 mm

TYP DB/P

**Product number** 90038

**Weight** 3.57kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

## Product description

- made of Polyglas-polyester material
- reinforced with fibreglass
- colour: red
- self extinguishing
- operating temperature:  $-40\text{ °C} < T < +130\text{ °C}$
- fire resistance: UL94-V0
- UM = max. permissible operating voltage

## Product properties

|  |  |
|--|--|
| <b>SW</b>                              | 41 mm  |
| <b>max. pressure-carrying capacity</b> | 80 kN  |
| <b>Typ</b>                             | DB/P 35  |
| <b>Colour</b>                          | red  |
| <b>Insulation material properties</b>  | self-extinguishing , Reinforced with glass fiber |
| <b>d1</b>                              | 35 mm  |
| <b>Insulation material</b>             | Polyglass-polyester compound                     |
| <b>Flame retardancy</b>                | UL 94 V-0  |
| <b>Threaded bolt material</b>          | Galvanized brass                                 |
| <b>Temperature resistant</b>           | -40 °C – 130 °C                                  |
| <b>max. pulling force</b>              | 11 kN  |
| <b>Creep strength</b>                  | 10 kV  |
| <b>A</b>                               | 9 mm   |
| <b>Thread (M)</b>                      | M6   |
| <b>H</b>                               | 35 mm  |
| <b>Discharge voltage</b>               | 35 kV  |
| <b>max. bending force</b>              | 8 kN   |
| <b>max. indicate torque</b>            | 8,9 Nm   |
| <b>U_M</b>                             | 1000 V   |
| <b>Type of packaging</b>               | 36   |

## More images

