

# HIL-SHRINK® 3:1 Heat Shrinkable Tubing, 18,0/6,0 black

Abschnitte

**Product number** 30440 L

**Weight** 0.121kg



Illustrations are for reference only.  
Technical specifications may vary and  
are subject to change without notice.

## Product description

Thin wall semi rigid heat shrinkable tubings, with adhesive inner liner.

- shrink ratio: 3:1
- permanent operating temperature: -55 °C up to +110 °C
- material: polyolefin cross-linked
- shrink temperature: 100 °C

## Product properties

|   |   |
|---|---|
| <b>Version</b>                          | sections  |
| <b>Continuous operating temperature</b> | -55 °C - 110 °C   |
| <b>Shrink ratio</b>                     | 3:1   |
| <b>Colour</b>                           | black   |
| <b>Section length</b>                   | 1 m   |
| <b>Type of packaging</b>                | 1   |
| <b>material properties</b>              | semi-rigid , with hot-melt adhesive coating on the inside , self-extinguishing , halogen-free |
| <b>Shrinking temperature</b>            | 100 °C  |
| <b>Material</b>                         | Polyolefin radiation cross-linked   |
| <b>min. at delivery Ø D</b>             | 18 mm   |
| <b>max after shrink operation Ø d</b>   | 6 mm  |
| <b>Flexibility</b>                      | thin-walled   |
| <b>Glue</b>                             | 0,6 mm  |
| <b>Excess length</b>                    | T   |
| <b>Huges after shrink op. s</b>         | 2,0 mm  |

## More images

