

## HP-ECO Iso insulators for low voltage, M12, black, 50 mm

ECO Isolatoren

**Product number** 91527

**Weight** 3.651kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

### Product description

- **Insulation:**
  - thermosetting polyester reinforced with 20% fiberglass
  - self-extinguishing: V0-UL94
  - colour: Red RAL 3031
- **Threaded inserts:**
  - galvanized steel
- **Final product:**
  - rated voltage: 1000 V AC/1500 V DC
  - working temperature: -40 °C up to +130 °C

## Product properties

<b>D</b>	40 mm
<b>CH</b>	50 mm
<b>Threaded bolt material</b>	Galvanized steel
<b>Colour</b>	red
<b>Typ</b>	ECO
<b>Insulation material properties</b>	self-extinguishing , reinforced with 20 % glass fiber
<b>f</b>	15 mm
<b>Thread (M)</b>	M12
<b>Flame retardancy</b>	UL 94 V-0
<b>Temperature resistant</b>	-40 °C – 130 °C
<b>Insulation material</b>	Thermosetting polyester resin
<b>Type of packaging</b>	25
<b>e</b>	12 mm
<b>H</b>	50 mm
<b>Rated voltage DC</b>	1500 V
<b>R.F.</b>	8,5 kN
<b>R.C.</b>	130 kN
<b>R.T.</b>	20,0 kN
<b>Nominal voltage AC</b>	1000 V

## More images

