

# HIL-QUICK® Ring Terminal, insulated, Polycarbonate unbrazed, A 2,5 - 1,0, 1000 pcs. | 1000

Ringform Quetschkabelschuhe Polycarbonat Isolierung

**Product number** 10001 SQ

**Weight** 0.695kg



Illustrations are for reference only.  
Technical specifications may vary and  
are subject to change without notice.

## Product description

- with flared insulation
- suitable for harmonised lines
- insulation: polycarbonate unbrazed
- temperature range: -10 °C up to 105 °C
- zero halogen
- UL approved

## Product properties

<b>Brand</b>	Hil-Quick®
<b>Colour</b>	red
<b>l</b>	17,3 mm
<b>d4</b>	4,3 mm
<b>a1</b>	5 mm
<b>Material thickness</b>	0,8 mm
<b>Nominal size</b>	A 2,5 - 1 DIN
<b>UL-Approval</b>	Yes
<b>Nominal cross section</b>	0,5 - 1,5 mm <sup>2</sup>
<b>Temperature resistant</b>	-10 °C - 105 °C
<b>Type of packaging</b>	1000
<b>d3</b>	6 mm
<b>a2</b>	11,3 mm
<b>Insulation material</b>	Polycarbonate
<b>Version</b>	unsoldered
<b>d2</b>	2,7 mm
<b>Insulation material properties</b>	halogen-free

## More images

