

## HILPRESS-METEX® cable screw glands, with long thread and stress relief, grey, M 40 x 1,5 PA | gray

METEX IP68 mit langem Anschlußgewinde

**Product number** 51534 L

**Weight** 0.728kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

### Product description

Integrated sealing, no O-ring necessary (M12 x 1,5 - M32 x 1,5). Only for smooth surfaces, otherwise the use of a sealing ring is recommended.

- Standard: EN 62444
- material: polyamide
- protection spec.: IP 68 up to 5 bar (30 min.)
- temperature resistance: -40 °C up to max. +100 °C
- flame protection: +750 °C
- gasket: EPDM
- halogen-free
- UL-approved

## Product properties

<b>H</b>	58 - 71 mm
<b>Sealing insert material</b>	EPDM
<b>Protection spec.</b>	IP 68
<b>UL-Approval</b>	Yes
<b>Temperature resistant</b>	-40 °C – 100 °C
<b>min. - max. cable diameter</b>	16 - 28 mm
<b>Material</b>	Polyamide
<b>Type of packaging</b>	10
<b>Thread (AG)</b>	M 40 x 1,5
<b>Version</b>	with long connection thread
<b>Thread type</b>	metric
<b>Colour</b>	gray
<b>Key size</b>	46 mm
<b>GL</b>	18 mm
<b>material properties</b>	halogen-free

## More images

