

# HIL-SHRINK® 2:1 Heat Shrinkable Tubing, not sel-extinguishing 1,2/0,6 clear | transparent

Box

**Product number** 30097

**Weight** 0.252kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

## Product description

Thin wall flexible heat shrinkable tubings, self extinguishing acc. to UL 224, on small spools in dispenser box

- shrink ratio: 2:1
- permanent operating temperature: -55 °C up to +125 °C
- material: polyolefin cross-linked
- shrink temperature: +120 °C

### Further information:

- ATTENTION: the transparent tubings are not self extinguishing!

## Product properties

|                                         |                                   |
|-----------------------------------------|-----------------------------------|
| <b>Shrinking temperature</b>            | 120 °C                            |
| <b>min. at delivery Ø D</b>             | 1,2 mm                            |
| <b>Huges after shrink op. s</b>         | 0,45 mm                           |
| <b>Type of packaging</b>                | 1                                 |
| <b>Shrink ratio</b>                     | 2:1                               |
| <b>min. at delivery Ø D</b>             | 3/64 Zoll                         |
| <b>Material</b>                         | Polyolefin radiation cross-linked |
| <b>Continuous operating temperature</b> | -55 °C – 125 °C                   |
| <b>Flexibility</b>                      | thin-walled                       |
| <b>Colour</b>                           | transparent                       |
| <b>Coil size</b>                        | 15 m/Box                          |
| <b>Version</b>                          | Box                               |
| <b>max after shrink operation Ø d</b>   | 0,6 mm                            |

## More images

